



#### Light source

#### Work equipment

#### Connected load

#### Power consumption

#### Standby

#### Power factor

#### Luminous flux

#### Luminous efficiency <sup>1)</sup>

#### Light type/-color

#### Colour temperatur

#### Color rendering index

#### Light distribution

#### Chromaticity tolerance LED

#### Glare control

#### Luminance (L65)

#### UGR class (4H 8H; EN 12464-1)

#### System of protection/Class

#### Technology

#### Operation

#### Housing

#### Light source cover

#### Dimming Range

#### Mains lead

#### Fastening

#### Life expectancy LED

#### Energy efficiency class

#### EAN

#### Weight without/incl. packaging

#### Dimensions (dimensional drawing)

#### Packaging dimensions

#### Special features

#### LED

Adjustable electronic ballast, digital DALI

220 - 240 V; 50 Hz; 60 Hz

ca. 29 W

ca. 0,15 W

env. 0,98

approx. 3.750 lm

approx. 129 lm/W

Warm white

approx. 3.000 K

CRI ≥ 80

Direct/indirect; approx. 40 %

< 3 SDCM

Prism aperture

≤ 2.700 cd/m<sup>2</sup>

≤ 16

IP 40

Continuously dimmable

External

Sectional aluminium; Silver

Acrylic (PMMA); Clear

1-100%

ca. 2 m; With free stranded wires; Start luminaire

Steel cable 0.3 - 0.7 m

L90B50 50.000h

C

4013330029906

ca. 4,9 kg; 6,4 kg

L=1408mm

ca. 1.600 mm; 190 mm; 120 mm

Flicker-free; Start luminaire with mains connection;  
DALI Load 1x; Suitable as emergency lighting;  
Through-wired, up to 18 m on one mains  
connection; Mechanical and electrical connection  
of the individual modules without tools

<sup>1)</sup> For luminaires with separate control gear, the luminous efficacy refers to the luminaire head without control g