



Light source
Work equipment
Connected load
Power consumption
Standby
Power factor
Luminous flux
Luminous efficiency ¹⁾
Light type/-color
Colour temperatur
Color rendering index
Light distribution
Chromaticity tolerance LED
Glare control
Luminance (L65)
UGR class (4H 8H; EN 12464-1)
System of protection/Class
Technology
Operation
Housing
Light source cover
Dimming Range
Fastening
Configuration
Life expectancy LED
Energy efficiency class
EAN
Weight without/incl. packaging
Packaging dimensions
Special features

LED
Adjustable electronic ballast, digital DALI
220 - 240 V; 50 Hz; 60 Hz
ca. 23 W
ca. 0,2 W
env. 0,970
approx. 3.150 lm
approx. 136 lm/W
Cold white
approx. 4.000 K
CRI ≥ 80
Direct/indirect; approx. 40 %
< 3 SDCM
Prism aperture
≤ 2.700 cd/m²
≤ 16
IP 40
Continuously dimmable
External
Sectional aluminium; White
Acrylic (PMMA); Clear
1-100%
Steel cable 0.3 - 0.7 m
Middle luminaire
L90B50 50.000h
C
4013330051846
ca. 4,5 kg; 5,7 kg
ca. 1.310 mm; 190 mm; 120 mm
Flicker-free; DALI Load 1x; Suitable as emergency lighting; Through-wired, up to 18 m on one mains connection; Mechanical and electrical connection of the individual modules without tools; 90° rerouting on the left side; Continuous light without dark z; TouchDIM - dimming via standard switch

¹⁾ For luminaires with separate control gear, the luminous efficacy refers to the luminaire head without control g