



#### Light source

#### Work equipment

#### Connected load

#### Power consumption

#### Standby

#### Power factor

#### Luminous flux

#### Luminous efficiency <sup>1)</sup>

#### Light type/-color

#### Colour temperatur

#### Color rendering index

#### Light distribution

#### Chromaticity tolerance LED

#### Glare control

#### Luminance (L65)

#### UGR class (4H 8H; EN 12464-1)

#### System of protection/Class

#### Technology

#### Operation

#### Housing

#### Light source cover

#### Dimming Range

#### Fastening

#### Configuration

#### Life expectancy LED

#### Energy efficiency class

#### EAN

#### Weight without/incl. packaging

#### Dimensions (dimensional drawing)

#### Packaging dimensions

#### Special features

#### LED

Adjustable electronic ballast, digital DALI

220 - 240 V; 50 Hz; 60 Hz

ca. 23 W

ca. 0,2 W

env. 0,970

approx. 3.000 lm

approx. 130 lm/W

Warm white

approx. 3.000 K

CRI ≥ 80

Direct/indirect; approx. 40 %

< 3 SDCM

Prism aperture

≤ 2.700 cd/m²

≤ 16

IP 40

Continuously dimmable

External

Sectional aluminium; Silver

Acrylic (PMMA); Clear

1-100%

Steel cable 0.3 - 0.7 m

Middle luminaire

L90B50 50.000h

C

4013330052256

ca. 4,5 kg; 5,7 kg

L=600mm

ca. 1.310 mm; 190 mm; 120 mm

Flicker-free; DALI Load 1x; Suitable as emergency lighting; Through-wired, up to 18 m on one mains connection; Mechanical and electrical connection of the individual modules without tools; 90° rerouting on the right side; Continuous light without dark zone; TouchDIM - dimming via standard switch

<sup>1)</sup> For luminaires with separate control gear, the luminous efficacy refers to the luminaire head without control gear