



**Light source**  
**Work equipment**  
**Connected load**  
**Power consumption**  
**Standby**  
**Power factor**  
**Luminous flux**  
**Luminous efficiency <sup>1)</sup>**  
**Light type/-color**  
**Colour temperatur**  
**Color rendering index**  
**Light distribution**  
**Chromaticity tolerance LED**  
**Glare control**  
**Luminance (L65)**  
**UGR class (4H 8H; EN 12464-1)**  
**System of protection/Class**  
**Technology**  
**Operation**  
**Housing**  
**Light source cover**  
**Dimming Range**  
**Fastening**  
**Configuration**  
**Life expectancy LED**  
**Energy efficiency class**  
**EAN**  
**Weight without/incl. packaging**  
**Packaging dimensions**  
**Special features**

LED  
Adjustable electronic ballast, digital DALI  
220 - 240 V; 50 Hz; 60 Hz  
ca. 32 W  
ca. 0,25 W  
env. 0,970  
approx. 3.150 lm  
approx. 98 lm/W  
Cold white  
approx. 2.700 - 6.500 K  
CRI ≥ 90  
Direct/indirect; approx. 40 %  
< 3 SDCM  
Prism aperture  
≤ 2.700 cd/m<sup>2</sup>  
≤ 16  
IP 40  
Continuously dimmable  
External  
Sectional aluminium; Silver  
Acrylic (PMMA); Clear  
3-100%  
Steel cable 0.3 - 0.7 m  
Middle luminaire  
L90B50 50.000h  
C  
4013330052317  
ca. 4,6 kg; 5,8 kg  
ca. 1.310 mm; 190 mm; 120 mm  
Flicker-free; DALI Load 1x; Suitable as emergency lighting; Through-wired, up to 18 m on one mains connection; Mechanical and electrical connection of the individual modules without tools; 90° rerouting on the right side; Continuous light without dark zone; External control required for Dali Device type 8; Constant colour temperature over the whole dimming range; Constant luminous flux between 2700 and 6500 K; Specified values at approx. 4000 K

<sup>1)</sup> For luminaires with separate control gear, the luminous efficacy refers to the luminaire head without control gear