



| | |
|--|---|
| Light source | LED |
| Work equipment | Adjustable electronic ballast, digital DALI |
| Connected load | 220 - 240 V; 50 Hz; 60 Hz |
| Power consumption | ca. 26 W |
| Standby | ca. 0,15 W |
| Power factor | env. 0,980 |
| Luminous flux | approx. 2.650 lm |
| Luminous efficiency ¹⁾ | approx. 101 lm/W |
| Light type/-color | Warm white |
| Colour temperatur | approx. 3.000 K |
| Color rendering index | CRI ≥ 80 |
| Light distribution | Direct; approx. 100 % |
| Chromaticity tolerance LED | < 3 SDCM |
| Glare control | Prism aperture |
| Luminance (L65) | ≤ 3.000 cd/m ² |
| UGR class (4H 8H; EN 12464-1) | ≤ 19 |
| System of protection/Class | IP 40 |
| Technology | Continuously dimmable |
| Operation | External |
| Housing | Sectional aluminium; White |
| Light source cover | Acrylic (PMMA); Clear |
| Mains lead | With free stranded wires |
| Fastening | Steel cable 0.3 - 0.7 m |
| Life expectancy LED | L90B50 50.000h |
| Energy efficiency class | C |
| EAN | 4013330034184 |
| Weight without/incl. packaging | ca. 7,3 kg; 9,6 kg |
| Dimensions (dimensional drawing) | L=2244mm |
| Packaging dimensions | ca. 2.410 mm; 190 mm; 120 mm |
| Special features | Flicker-free; DALI Load 1x; Suitable as emergency lighting; Through-wired, up to 18 m on one mains connection; Mechanical and electrical connection of the individual modules without tools; TouchDIM - dimming via standard switch |

¹⁾ For luminaires with separate control gear, the luminous efficacy refers to the luminaire head without control gear