






Light source

Work equipment

Connected load

Power consumption

Standby

Power factor

Luminous flux

Luminous efficiency ¹⁾

Light type/-color

Colour temperatur

Color rendering index

Light distribution

Beam angle

Chromaticity tolerance LED

Glare control

Luminance (L65)

UGR class (4H 8H; EN 12464-1)

System of protection/Class

Technology

Operation

Housing

Light source cover

Dimming Range

Mains lead

Fastening

Life expectancy LED

Energy efficiency class

EAN

Weight without/incl. packaging

Dimensions (dimensional drawing)

Packaging dimensions

Special features

LED

Adjustable electronic ballast, digital DALI

220 - 240 V; 50 Hz; 60 Hz

ca. 26 W

ca. 0,15 W

env. 0,980

approx. 2.650 lm

approx. 101 lm/W

Warm white

approx. 3.000 K

CRI ≥ 80

Direct; approx. 100 %

86°

< 3 SDCM

Prism aperture

≤ 3.000 cd/m²

≤ 19

IP 40

Continuously dimmable

External

Sectional aluminium; White

Acrylic (PMMA); Clear

1-100%

ca. 2 m; With free stranded wires; Single Luminaire

Steel cable 0.3 - 0.7 m

L90B50 50.000h

C

4013330034160

ca. 7,3 kg; 9,6 kg

L=2256mm

ca. 2.410 mm; 190 mm; 120 mm

Flicker-free; DALI Load 1x; Suitable as emergency lighting; TouchDIM - dimming via standard switch

¹⁾ For luminaires with separate control gear, the luminous efficacy refers to the luminaire head without control g