



## Light source

## Work equipment

## Connected load

## Power consumption

## Standby

## Power factor

## Luminous flux

## Luminous efficiency <sup>1)</sup>

## Light type/-color

## Colour temperatur

## Color rendering index

## Light distribution

## Chromaticity tolerance LED

## Glare control

## Luminance (L65)

## UGR class (4H 8H; EN 12464-1)

## System of protection/Class

## Technology

## Operation

## Housing

## Light source cover

## Mains lead

## Fastening

## Life expectancy LED

## Energy efficiency class

## EAN

## Weight without/incl. packaging

## Dimensions (dimensional drawing)

## Packaging dimensions

## Special features

## LED

Adjustable electronic ballast, digital DALI

220 - 240 V; 50 Hz; 60 Hz

ca. 13 W

ca. 0,2 W

env. 0,970

approx. 1.300 lm

approx. 100 lm/W

Warm white

approx. 3.000 K

CRI  $\geq$  80

Direct; approx. 100 %

< 3 SDCM

Prism aperture

$\leq$  3.000 cd/m<sup>2</sup>

$\leq$  19

IP 40

Continuously dimmable

External

Sectional aluminium; Silver

Acrylic (PMMA); Clear

With free stranded wires

Steel cable 0.3 - 0.7 m

L90B50 50.000h

C

4013330036645

ca. 3,8 kg; 5 kg

L=1128mm

ca. 1.310 mm; 190 mm; 120 mm

Flicker-free; DALI Load 1x; Suitable as emergency lighting; Through-wired, up to 18 m on one mains connection; Mechanical and electrical connection of the individual modules without tools; TouchDIM - dimming via standard switch

<sup>1)</sup> For luminaires with separate control gear, the luminous efficacy refers to the luminaire head without control g