



H	$\Phi$ : 1000 lm	E   0°	D
0.50 m	C0-C180: 86°	2188 lx	C90-C270: 87° 0.93 m   0.95 m
1.00 m		547 lx	1.85 m   1.90 m
1.50 m		243 lx	2.78 m   2.86 m
2.00 m		137 lx	3.70 m   3.81 m
2.50 m		87.5 lx	4.63 m   4.76 m
3.00 m		60.8 lx	5.56 m   5.71 m
3.50 m		44.7 lx	6.48 m   6.67 m

## Work equipment

### Connected load

### Power consumption

### Standby

### Power factor

### Luminous flux

### Luminous efficiency <sup>1)</sup>

### Light type/color

### Colour temperatur

### Color rendering index

### Light distribution

### Beam angle

### Chromaticity tolerance LED

### Glare control

### Luminance (L65)

### UGR class (4H 8H; EN 12464-1)

### System of protection/Class <sup>2)</sup>

### Technology

### Operation

### Housing

### Light source cover

### Mains lead

### Design

### Fastening

### Life expectancy LED

### EAN

### Weight without/incl. packaging

### Dimensions (dimensional drawing)

### Packaging dimensions

### Special features

Adjustable electronic ballast, digital DALI

220 - 240 V; 50 Hz; 60 Hz

ca. 9,5 W

ca. 0,2 W

env. 0,97

approx. 1.000 lm

approx. 105 lm/W

Cold white

approx. 4.000 K

CRI ≥ 80

Direct; approx. 100 %

86°

< 3 SDCM

Prism aperture

≤ 3.000 cd/m<sup>2</sup>

≤ 19

IP 40; 22; I

Continuously dimmable

External

Sectional aluminium; White

Acrylic (PMMA); Clear

Connector

Integrated version

Fastening bow

L90B50 50.000h

4013330079116

ca. 3,1 kg; 3,5 kg

L=854mm

ca. 990 mm; 190 mm; 115 mm

Flicker-free; DALI Load 1x; Suitable as emergency lighting; TouchDIM - dimming via standard switch

<sup>1)</sup> For luminaires with separate control gear, the luminous efficacy refers to the luminaire head without control gear  
<sup>2)</sup> Higher degree of protection when installed.