



## Work equipment

### Connected load

### Power consumption

### Standby

### Power factor

### Luminous flux

### Luminous efficiency <sup>1)</sup>

### Light type/-color

### Colour temperatur

### Color rendering index

### Light distribution

### Chromaticity tolerance LED

### Glare control

### Luminance (L65)

### UGR class (4H 8H; EN 12464-1)

### Technology

### Operation

### Housing

### Light source cover

### Mains lead

### Design

### Fastening

### Life expectancy LED

### EAN

### Weight without/incl. packaging

### Packaging dimensions

### Special features

Adjustable electronic ballast, digital DALI

220 - 240 V; 50 Hz; 60 Hz

ca. 17 W

ca. 0,25 W

env. 0,97

approx. 2.250 lm

approx. 132 lm/W

Warm white

approx. 3.000 K

CRI ≥ 80

Direct/indirect; approx. 40 %

< 3 SDCM

Prism aperture

≤ 2.700 cd/m<sup>2</sup>

≤ 16

Continuously dimmable

External

Sectional aluminium; White

Acrylic (PMMA); Clear

Connector

mounted version

Mounting rail

L90B50 50.000h

4013330081256

ca. 3,9 kg

ca. 1.000 mm; 190 mm; 120 mm

Flicker-free; DALI Load 1x; Suitable as emergency lighting; TouchDIM - dimming via standard switch

<sup>1)</sup> For luminaires with separate control gear, the luminous efficacy refers to the luminaire head without control gear