



H	Φ : 4600 lm	E 0°	D
2.00 m		422 lx	4.35 m 4.78 m
4.00 m		106 lx	8.69 m 9.57 m
6.00 m		46.9 lx	13.0 m 14.4 m
8.00 m		26.4 lx	17.4 m 19.1 m
10.0 m		16.9 lx	21.7 m 23.9 m

Light source	LED; IK06
Work equipment	Adjustable electronic ballast, digital DALI
Connected load	220 - 240 V; 50 Hz; 60 Hz
Power consumption	ca. 28 W
Lens	W optics, wide beam
Luminous flux	approx. 4.600 lm
Light type/-color	Cold white
Colour temperatur	approx. 5.000 K
Color rendering index	CRI \geq 80
Light distribution	Direct
Direct ratio	approx. 100 %
Beam angle	95° / 100°
Chromaticity tolerance LED	< 3 SDCM
Glare control	Optics
Luminance (L65)	\leq 14.900 cd/m ²
UGR class (4H 8H; EN 12464-1)	\leq 25
System of protection/Class	IP 54; I
Technology	Continuously dimmable
Housing	Aluminium; Powder coatet; White
Light source cover	Acrylic (PMMA); Satine
Fastening	Available separately
Minimum ambient temperature	-25 °C
Maximum ambient temperature	55 °C
Life expectancy LED	L80B50 50.000h
EAN	4013330006457
Weight without/incl. packaging	ca. 1,9 kg; 2,1 kg
Packaging dimensions	ca. 1.520 mm; 75 mm; 83 mm