


CEE 7/VII

D43 ↓ 13.0% ↑ 87.0%



**Light source**

**Work equipment**

**Connected load**

**Power consumption**

**Power factor**

**Luminous flux**

**Luminous efficiency**

**Light type/-color**

**Colour temperatur**

**Color rendering index**

**Light distribution**

**Direct ratio**

**Chromaticity tolerance LED**

**Glare control**

**Unified glare rating (4H 8H) <sup>1)</sup>**

**System of protection**

**Class of protection**

**Technology**

**Operation**

**Housing**

**Light source cover**

**Arm**

**Luminaire base**

**Weight (net)**

**Mains lead**

**Fastening**

**Dimensions**

**Life expectancy LED**

**Special features**

LED

Electronic ballast DALI

220 - 240 V; AC; 50 Hz; 60 Hz

ca. 223 W; 428 W

env. 0,966

approx. 32.000 lm

approx. 143 lm/W

Cold white

approx. 4.000 K

CRI ≥ 80

Direct/indirect

approx. 13 %

< 3 SDCM

005

≤ 16

IP 20

I

Presence and daylight sensor control (PIR); DALI;

Touch DIM

Wireless switch

Aluminium/plastic; Powder coatet; White

Acrylic (PMMA)

Steel tube; Powder-coated; Tubular section

upright; White

Rectangular flat

ca. 38 kg

ca. 3 m; Mains plug; CEE 7/VII

Floor standing base

2.024 mm

L80B50 60.000h

Asymmetric radiation; Flicker-free; App control;  
Direct and indirect lighting component with edge  
light and light guide technology for a  
homogeneous light exit; PIR movement and  
daylight sensor; TALK Bluetooth; Magnetic control  
panel, freely positionable

<sup>1)</sup> according to DIN EN 12464-1:2021