Free-standing luminaire LAVIGO DPS 9000/840/D/G2

121836000-00807247



CEE 7/VII



Light source	LED
Work equipment	Electronic ballast
Connected load	220 - 240 V; AC; 50 Hz; 60 Hz
Power consumption	ca. 63 W
Standby	ca. 0,5 W
Power factor	env. 0,91
Luminous flux	approx. 8.950 lm
Luminous efficiency [1)]	approx. 142 lm/W
Light type/-color	Cold white
Colour temperatur	approx. 4.000 K
Color rendering index	CRI ≥ 80
Light distribution	Direct/indirect; approx. 20 %
Chromaticity tolerance LED	< 3 SDCM
Glare control	Prism aperture
Luminance (L65)	≤ 3.000 cd/m²
UGR class (4H 8H; EN 12464-1)	≤ 16
System of protection/Class	IP 20; I
Technology	Continuously dimmable
Operation	Multi-function switch
Housing	Steel/plastic; Painted; White
Light source cover	Acrylic (PMMA); Satine
Arm	Steel tube; Painted; Tubular section upright; White
Luminaire base	C-form flat
Mains lead	ca. 3 m; Mains plug; CEE 7/VII
Fastening	Floor standing base
Decorative contrast side parts	Flint grey
Life expectancy LED	L80B50 60.000h
Energy efficiency class	C; D
EPREL number of lightsources	1504142; 1951837; 887125
EAN	4013330123949
Weight without/incl. packaging	ca. 19,7 kg
Special features	Separated, direct and indirect light individually adjustable; Flicker-free; Cradle to Cradle Certified TM; Direct light component with edge light and light-guide technology for homogenous light exit; Luminaire head detachable

[1)] For luminaires with separate control gear, the luminous efficacy refers to the luminaire head without control g

Errors and technical changes excepted. Images can vary from original.
Photometric and electrical data may vary due to component tolerances.

www.waldmann.com
© 21/10/2024 H.Waldmann GmbH & Co. KG