


CEE 7/VII

D53 ↓ 11.5% ↑ 88.5% Φ: 15250 lm
UGR 4H 8H: <10 / <10



Light source

Work equipment

Connected load

Power consumption

Power factor

Luminous flux

Luminous efficiency

Light type/-color

Colour temperatur

Color rendering index

Light distribution

Direct ratio

Chromaticity tolerance LED

Glare control

Luminance (L65)

Unified glare rating (4H 8H) ¹⁾

System of protection

Class of protection

Technology

Operation

Housing

Light source cover

Arm

Luminaire base

Weight (net)

Mains lead

Fastening

Dimensions

Decorative contrast side parts

Life expectancy LED

Special features

LED

Electronic ballast

220 - 240 V; AC; 50 Hz; 60 Hz

ca. 210 W

env. 0,966

approx. 30.500 lm

approx. 145 lm/W

Cold white

approx. 4.000 K

CRI ≥ 80

Direct/indirect

approx. 12 %

< 3 SDCM

Conical prismatic screen

≤ 3.000 cd/m²

≤ 16

IP 20

I

Presence and daylight sensor control (PIR); DALI

Multi-function switch; Touch-LED

Steel/plastic; Painted; Silver metallic

Acrylic (PMMA); Satine

Steel tube; Painted; Tubular section upright; Silver metallic

Rectangular flat

ca. 27 kg

ca. 3 m; Mains plug; CEE 7/VII

Floor standing base

2.035 mm

Metallic silver

L80B50 60.000h

Integrated light and presence sensor PIR;
Asymmetric radiation; Separated, direct and indirect light individually adjustable; Retrofittable with TALK module; Flicker-free; Direct light component with edge light and light-guide technology for homogenous light exit; Luminaire head detachable

¹⁾ according to DIN EN 12464-1:2021