



A50 100.0% Φ : 580 lm



60 x 60 cm Φ : 580 lm

Em: 803 lx
Emax: 1215 lx
Emin: 416 lx



Φ : 580 lm $E 0^\circ$

C0-C180: 88°		C90-C270: 89°	
0.25 m	4991 lx	0.48 m 0.49 m	
0.50 m	1248 lx	0.96 m 0.98 m	
0.75 m	555 lx	1.44 m 1.47 m	
1.00 m	312 lx	1.92 m 1.96 m	

light source
work equipment
connected load
secondary tension
power consumption
sec. power consumption
luminous flux
luminous efficiency
light type/color
colour temperatur
color rendering index
light distribution
direct ratio
beam angle
chromaticity tolerance LED
glare control
system of protection
class of protection
technology
operation
housing
cover
arm
weight (net)
mains lead
fastening
special features

LED
electronic plug-in transformer
100 - 240 V; Wechselstrom (AC); 50 Hz; 60 Hz
24 V
ca. 7 W
ca. 6 W
approx. 580 lm
approx. 96 lm/W
warm white
approx. 3.000 K
CRI > 90; R9 > 50
direct; symmetric
approx. 100 %
90°
< 3 SDCM
plastic reflector
IP 20
II with plug-in power supply, III without plug-in power supply
continuously dimmable; no notice
push button
aluminium; painted; black
clear; plastic
Jet black
ca. 1 kg
ca. 3 m; mains plug; CEE 7/XVI; BS 1363; NEMA 1-15P
adaptor (accessory); tap16; table base (accessory); table clamp (accessory)
automatic switchoff adjustable; behaviour at net recovery adjustable; push button in luminaire head

