



Light source	LED
Work equipment	Electronic ballast DALI
Connected load	220 - 240 V; AC; 50 Hz; 60 Hz
Power consumption	ca. 112 W
Standby	ca. 0,5 W
Power factor	env. 0,940
Luminous flux	approx. 16.450 lm
Luminous efficiency ¹⁾	approx. 146 lm/W
Light type/-color	Cold white
Colour temperatur	approx. 4.000 K
Color rendering index	CRI ≥ 80
Light distribution	Direct/indirect; approx. 11 %
Chromaticity tolerance LED	< 3 SDCM
Glare control	Prism aperture
Luminance (L65)	≤ 2.800 cd/m ²
UGR class (4H 8H; EN 12464-1)	≤ 16
System of protection/Class	IP 20; I
Technology	Presence and daylight sensor control (PIR)
Operation	Multi-function switch
Housing	Steel/plastic; Powder coatet; White
Light source cover	Polycarbonate (PC); Clear; Structured
Arm	Steel tube; Powder-coated; Tubular section upright; White
Luminaire base	C-form flat
Mains lead	ca. 3 m; Mains plug; CEE 7/VII
Fastening	Floor standing base
Decorative contrast side parts	Flint grey
Life expectancy LED	L80B50 60.000h
Energy efficiency class	C
EPREL number of lightsources	1288568; 1288571; 887125
EAN	4013330017224
Weight without/incl. packaging	ca. 21,4 kg; 25,1 kg
Special features	Integrated light and presence sensor PIR; Separated, direct and indirect light individually adjustable; Retrofittable with TALK module; Flicker-free; Cradle to Cradle Certified TM; Direct light component with edge light and light-guide technology for homogenous light exit; Luminaire head detachable

¹⁾ For luminaires with separate control gear, the luminous efficacy refers to the luminaire head without control g