



**Light source**  
**Work equipment**  
**Connected load**  
**Power consumption**  
**Standby**  
**Power factor**  
**Luminous flux**  
**Luminous efficiency <sup>1)</sup>**  
**Light type/-color**  
**Colour temperatur**  
**Color rendering index**  
**Light distribution**  
**Chromaticity tolerance LED**  
**Glare control**  
**Luminance (L65)**  
**UGR class (4H 8H; EN 12464-1)**  
**System of protection/Class**  
**Technology**  
**Operation**  
**Housing**  
**Light source cover**  
**Arm**  
**Luminaire base**  
**Mains lead**  
**Fastening**  
**Decorative contrast side parts**  
**Life expectancy LED**  
**Energy efficiency class**  
**EPREL number of lightsources**  
**EAN**  
**Weight without/incl. packaging**  
**Special features**

LED  
Electronic ballast  
220 - 240 V; AC; 50 Hz; 60 Hz  
ca. 113 W  
ca. 0,5 W  
env. 0,963  
approx. 16.150 lm  
approx. 142 lm/W  
Cold white  
approx. 4.000 K  
CRI ≥ 80  
Direct/indirect; approx. 11 %  
< 3 SDCM  
Prism aperture  
≤ 3.000 cd/m<sup>2</sup>  
≤ 16  
IP 20; I  
Presence and daylight sensor control (PIR)  
Multi-function switch  
Steel/plastic; Painted; Silver metallic  
Acrylic (PMMA); Satine  
Steel tube; Painted; Tubular section upright; Silver metallic  
C-form flat  
ca. 3 m; Mains plug; CEE 7/VII  
Floor standing base  
Flint grey  
L80B50 60.000h  
C; D  
1951837; 887125  
4013330018047  
ca. 19,7 kg  
Integrated light and presence sensor PIR;  
Separated, direct and indirect light individually  
adjustable; Retrofittable with TALK module; Flicker-  
free; Cradle to Cradle Certified TM; Direct light  
component with edge light and light-guide  
technology for homogenous light exit; Luminaire  
head detachable

<sup>1)</sup> For luminaires with separate control gear, the luminous efficacy refers to the luminaire head without control g