



Light source
Work equipment
Connected load
Power consumption
Standby
Power factor
Luminous flux
Luminous efficiency ¹⁾
Light type/-color
Colour temperatur
Color rendering index
Light distribution
Chromaticity tolerance LED
Glare control
Luminance (L65)
UGR class (4H 8H; EN 12464-1)
System of protection/Class
Technology
Operation
Housing
Light source cover
Arm
Luminaire base
Mains lead
Fastening
Decorative contrast side parts
Life expectancy LED
Energy efficiency class
EPREL number of lightsources
EAN
Weight without/incl. packaging
Special features

LED
Electronic ballast
220 - 240 V; AC; 50 Hz; 60 Hz
ca. 77 W
ca. 0,5 W
env. 0,93
approx. 11.650 lm
approx. 151 lm/W
Cold white
approx. 4.000 K
CRI ≥ 80
Direct/indirect; approx. 15 %
< 3 SDCM
Prism aperture
≤ 3.000 cd/m²
≤ 16
IP 20; I
Presence and daylight sensor control (PIR)
Multi-function switch
Steel/plastic; Painted; Silver metallic
Acrylic (PMMA); Satine
Steel tube; Painted; Tubular section upright; Silver metallic
C-form flat
ca. 3 m; Mains plug; CEE 7/VII
Floor standing base
Flint grey
L80B50 60.000h
C; D
1504142; 1951837; 887125
4013330103408
ca. 19,7 kg
Integrated light and presence sensor PIR;
Separated, direct and indirect light individually
adjustable; Retrofittable with TALK module; Flicker-
free; Cradle to Cradle Certified TM; Direct light
component with edge light and light-guide
technology for homogenous light exit; Luminaire
head detachable

¹⁾ For luminaires with separate control gear, the luminous efficacy refers to the luminaire head without control gear