


CEE 7/VII

D53 | 11.5% ↑ 88.5% Φ: 15250 lm
UGR 4H 8H: <10 / <10



Light source

Work equipment

Connected load

Power consumption

Power factor

Luminous flux

Luminous efficiency ¹⁾

Light type/-color

Colour temperatur

Color rendering index

Light distribution

Direct ratio

Chromaticity tolerance LED

Glare control

Luminance (L65)

UGR class (4H 8H; EN 12464-1)

System of protection

Class of protection

Technology

Operation

Emergency lighting

Housing

Light source cover

Arm

Luminaire base

Mains lead

Fastening

Decorative contrast side parts

Life expectancy LED

EAN

Weight (net)

Dimensions

Special features

LED

Electronic ballast

220 - 240 V; AC; 50 Hz; 60 Hz

ca. 210 W

env. 0,966

approx. 30.500 lm

approx. 145 lm/W

Cold white

approx. 4.000 K

CRI ≥ 80

Direct/indirect

approx. 12 %

< 3 SDCM

Prism aperture

≤ 3.000 cd/m²

≤ 16

IP 20

I

Presence and daylight sensor control (PIR); DALI

Multi-function switch; Touch-LED

none

Steel/plastic; Painted; White

Acrylic (PMMA); Satine

Steel tube; Painted; Tubular section upright; White

Rectangular flat

ca. 3 m; Mains plug; CEE 7/VII

Floor standing base

Flint grey

L80B50 60.000h

4013330118808

ca. 28,4 kg

2.035 mm

Integrated light and presence sensor PIR;
Asymmetric radiation; Separated, direct and
indirect light individually adjustable; Retrofittable
with TALK module; Flicker-free; Direct light
component with edge light and light-guide
technology for homogenous light exit; Luminaire
head detachable

¹⁾ For luminaires with separate control gear, the luminous efficacy refers to the luminaire head without control gear