


CEE 7/VII

**Light source****Work equipment****Connected load****Power consumption****Standby****Power factor****Luminous flux****Luminous efficiency <sup>1)</sup>****Light type/-color****Colour temperatur****Color rendering index****Light distribution****Chromaticity tolerance LED****Glare control****Luminance (L65)****UGR class (4H 8H; EN 12464-1)****System of protection/Class****Technology****Operation****Housing****Light source cover****Arm****Luminaire base****Mains lead****Fastening****Decorative contrast side parts****Life expectancy LED****Energy efficiency class****EPREL number of lightsources****EAN****Weight without/incl. packaging****Special features**

LED

Electronic ballast

220 - 240 V; AC; 50 Hz; 60 Hz

ca. 63 W

ca. 0,5 W

env. 0,91

approx. 8.950 lm

approx. 142 lm/W

Cold white

approx. 4.000 K

CRI ≥ 80

Direct/indirect; approx. 20 %

&lt; 3 SDCM

Prism aperture

≤ 3.000 cd/m<sup>2</sup>

≤ 16

IP 20; I

Presence and daylight sensor control (PIR)

Multi-function switch

Steel/plastic; Painted; Silver metallic

Acrylic (PMMA); Satine

Steel tube; Painted; Tubular section upright; Silver metallic

C-form flat

ca. 3 m; Mains plug; CEE 7/VII

Floor standing base

Flint grey

L80B50 60.000h

C; D

1951837; 887125

4013330017583

ca. 19,7 kg

Integrated light and presence sensor PIR;  
Separated, direct and indirect light individually  
adjustable; Retrofittable with TALK module; Flicker-  
free; Cradle to Cradle Certified TM; Direct light  
component with edge light and light-guide  
technology for homogenous light exit; Luminaire  
head detachable

<sup>1)</sup> For luminaires with separate control gear, the luminous efficacy refers to the luminaire head without control g