


CEE 7/VII

E53 | 8.4% ↑ 91.6% Φ : 20750 lm
 UGR 4H 8H: <10 / <10

**Light source****Work equipment****Connected load****Power consumption****Standby****Power factor****Luminous flux****Luminous efficiency ¹⁾****Light type/-color****Colour temperatur****Color rendering index****Light distribution****Chromaticity tolerance LED****Glare control****Luminance (L65)****UGR class (4H 8H; EN 12464-1)****System of protection/Class****Technology****Operation****Housing****Light source cover****Arm****Luminaire base****Mains lead****Fastening****Decorative contrast side parts****Life expectancy LED****Energy efficiency class****EPREL number of lightsources****EAN****Weight without/incl. packaging****Special features**

LED

Electronic ballast DALI

220 - 240 V; AC; 50 Hz; 60 Hz

ca. 142 W

ca. 0,5 W

env. 0,948

approx. 20.750 lm

approx. 146 lm/W

Cold white

approx. 4.000 K

CRI \geq 80

Direct/indirect; approx. 8,4 %

< 3 SDCM

Prism aperture

 \leq 2.800 cd/m² \leq 16

IP 20; I

Presence and daylight sensor control (PIR)

Multi-function switch

Steel/plastic; Powder coatet; Silver metallic

Polycarbonate (PC); Clear; Structured

Steel tube; Powder-coated; Tubular section

upright; Silver metallic

C-form flat

ca. 3 m; Mains plug; CEE 7/VII

Floor standing base

Flint grey

L80B50 60.000h

C

1288568; 1288571; 887125

4013330138653

ca. 15,4 kg; 21,4 kg

Integrated light and presence sensor PIR;
 Separated, direct and indirect light individually
 adjustable; Retrofittable with TALK module; Flicker-
 free; Cradle to Cradle Certified TM; Direct light
 component with edge light and light-guide
 technology for homogenous light exit; Luminaire
 head detachable

¹⁾ For luminaires with separate control gear, the luminous efficacy refers to the luminaire head without control g