



Light source

Work equipment

Connected load

Power consumption

Standby

Power factor

Luminous flux

Luminous efficiency ¹⁾

Light type/-color

Colour temperatur

Color rendering index

Light distribution

Chromaticity tolerance LED

Glare control

Luminance (L65)

UGR class (4H 8H; EN 12464-1)

System of protection/Class

Technology

Operation

Housing

Light source cover

Arm

Mains lead

Fastening

Minimum ambient temperature

Maximum ambient temperature

Decorative contrast side parts

Life expectancy LED

Energy efficiency class

EPREL number of lightsources

EAN

Weight without/incl. packaging

Special features

LED

Electronic ballast

220 - 240 V; AC; 50 Hz; 60 Hz

ca. 93 W

ca. 0,5 W

env. 0,943

approx. 14.050 lm

approx. 151 lm/W

Cold white

approx. 4.000 K

CRI ≥ 80

Direct/indirect; approx. 12 %

< 3 SDCM

Prism aperture

≤ 3.000 cd/m²

≤ 16

IP 20; I

Continuously dimmable

Multi-function switch

Steel/plastic; Painted; Silver metallic

Acrylic (PMMA); Satine

Steel tube; Painted; Tubular section upright; Silver metallic

ca. 3,7 m; Mains plug; CEE 7/VII

Socket; Table adaptor

25 °C

25 °C

Flint grey

L80B50 60.000h

C; D

1951837; 887125

4013330123765

ca. 9,5 kg; 11,9 kg

Separated, direct and indirect light individually adjustable; Flicker-free; Inclination of tubular section adjustable; Cradle to Cradle Certified TM; Direct light component with edge light and light-guide technology for homogenous light exit; Luminaire head detachable

¹⁾ For luminaires with separate control gear, the luminous efficacy refers to the luminaire head without control gear