



Light source	LED
Work equipment	Electronic ballast DALI
Connected load	220 - 240 V; AC; 50 Hz; 60 Hz
Power consumption	ca. 65 W
Standby	ca. 0,5 W
Power factor	env. 0,942
Luminous flux	approx. 9.350 lm
Luminous efficiency ¹⁾	approx. 143 lm/W
Light type/-color	Cold white
Colour temperatur	approx. 4.000 K
Color rendering index	CRI ≥ 80
Light distribution	Direct/indirect; approx. 19 %
Chromaticity tolerance LED	< 3 SDCM
Glare control	optical film; Prism aperture
Luminance (L65)	≤ 2.800 cd/m ²
UGR class (4H 8H; EN 12464-1)	≤ 16
System of protection/Class	IP 20; I
Technology	Presence and daylight sensor control (PIR)
Operation	External
Housing	Steel/plastic; Powder coatet; Silver metallic
Light source cover	Polycarbonate (PC); Clear
Mains lead	ca. 1 m; With free stranded wires; Single Luminaire
Fastening	Steel cable 0.3 - 0.7 m
Minimum ambient temperature	25 °C
Maximum ambient temperature	25 °C
Decorative contrast side parts	Flint grey
Energy efficiency class	C
EPREL number of lightsources	1288568; 1288571; 887125
EAN	4013330014605
Weight without/incl. packaging	ca. 7,5 kg; 8 kg
Packaging dimensions	ca. 1.350 mm; 290 mm; 110 mm
Special features	Integrated light and presence sensor PIR; Separated, direct and indirect light individually adjustable; Retrofittable with TALK module; Cradle to Cradle Certified TM; Direct light component with edge light and light-guide technology for homogenous light exit; Push button in luminaire head; Canopy colour (pure white)

¹⁾ For luminaires with separate control gear, the luminous efficacy refers to the luminaire head without control g