



Light source

Work equipment

Connected load

Power consumption

Standby

Power factor

Luminous flux

Luminous efficiency ¹⁾

Light type/-color

Colour temperatur

Color rendering index

Light distribution

Chromaticity tolerance LED

Glare control

Luminance (L65)

UGR class (4H 8H; EN 12464-1)

System of protection/Class

Technology

Operation

Housing

Light source cover

Mains lead

Fastening

Minimum ambient temperature

Maximum ambient temperature

Decorative contrast side parts

Energy efficiency class

EPREL number of lightsources

EAN

Weight without/incl. packaging

Packaging dimensions

Special features

LED

Electronic ballast DALI

220 - 240 V; AC; 50 Hz; 60 Hz

ca. 65 W

ca. 0,5 W

env. 0,942

approx. 9.350 lm

approx. 143 lm/W

Cold white

approx. 4.000 K

CRI ≥ 80

Direct/indirect; approx. 19 %

< 3 SDCM

optical film; Prism aperture

≤ 2.800 cd/m²

≤ 16

IP 20; I

Presence and daylight sensor control (PIR)

External

Steel/plastic; Powder coatet; White

Polycarbonate (PC); Clear

ca. 1 m; With free stranded wires; Single Luminaire

Steel cable 0.3 - 0.7 m

25 °C

25 °C

Flint grey

C

1288568; 1288571; 887125

4013330019174

ca. 7,5 kg; 8 kg

ca. 1.350 mm; 290 mm; 110 mm

Integrated light and presence sensor PIR;
Separated, direct and indirect light individually
adjustable; Retrofittable with TALK module; Cradle
to Cradle Certified TM; Direct light component with
edge light and light-guide technology for
homogenous light exit; Push button in luminaire
head; Canopy colour (pure white)

¹⁾ For luminaires with separate control gear, the luminous efficacy refers to the luminaire head without control g