



#### Light source

#### Work equipment

#### Connected load

#### Power consumption

#### Standby

#### Power factor

#### Luminous flux

#### Luminous efficiency <sup>1)</sup>

#### Light type/-color

#### Colour temperatur

#### Color rendering index

#### Light distribution

#### Chromaticity tolerance LED

#### Glare control

#### Luminance (L65)

#### UGR class (4H 8H; EN 12464-1)

#### System of protection/Class

#### Technology

#### Operation

#### Housing

#### Light source cover

#### Dimming Range

#### Mains lead

#### Fastening

#### Life expectancy LED

#### Energy efficiency class

#### EAN

#### Weight without/incl. packaging

#### Dimensions (dimensional drawing)

#### Packaging dimensions

#### Special features

LED

Electronic ballast

220 - 240 V; 50 Hz; 60 Hz

ca. 32 W

ca. 0,25 W

env. 0,970

approx. 3.150 lm

approx. 98 lm/W

Cold white

approx. 2.700 - 6.500 K

CRI ≥ 90

Direct/indirect; approx. 40 %

< 3 SDCM

Prism aperture

≤ 2.700 cd/m<sup>2</sup>

≤ 16

IP 40

Continuously dimmable

External

Sectional aluminium; Silver

Acrylic (PMMA); Clear

3-100%

ca. 2 m; With free stranded wires; Single Luminaire

Steel cable 0.3 - 0.7 m

L90B50 50.000h

C

4013330039455

ca. 4,2 kg; 5,4 kg

L=1134mm

ca. 1.310 mm; 190 mm; 120 mm

Flicker-free; DALI Load 1x; Suitable as emergency lighting; External control required for Dali Device type 8; Constant colour temperature over the whole dimming range; Constant luminous flux between 2700 and 6500 K; Specified values at approx. 4000 K

<sup>1)</sup> For luminaires with separate control gear, the luminous efficacy refers to the luminaire head without control gear