



**Light source**

**Work equipment**

**Connected load**

**Power consumption**

**Standby**

**Power factor**

**Luminous flux**

**Luminous efficiency <sup>1)</sup>**

**Light type/-color**

**Colour temperatur**

**Color rendering index**

**Light distribution**

**Chromaticity tolerance LED**

**Glare control**

**Luminance (L65)**

**UGR class (4H 8H; EN 12464-1)**

**System of protection/Class**

**Technology**

**Operation**

**Housing**

**Light source cover**

**Mains lead**

**Fastening**

**Energy efficiency class**

**EAN**

**Weight without/incl. packaging**

**Packaging dimensions**

**Special features**

LED

Electronic ballast

220 - 240 V; 50 Hz; 60 Hz

ca. 49 W

ca. 0,3 W

env. 0,950

approx. 7.000 lm

approx. 142 lm/W

Cold white

approx. 4.000 K

CRI ≥ 80

Direct/indirect; approx. 34 %

< 3 SDCM

Prism aperture

≤ 2.500 cd/m<sup>2</sup>

≤ 16

IP 20

Continuously dimmable

External

Silver

Acrylic (PMMA); Clear

ca. 1 m; With free stranded wires; Single Luminaire

Steel cable 0.3 - 0.7 m

E

4013330081645

ca. 7,5 kg; 8,6 kg

ca. 1.355 mm; 300 mm; 90 mm

Indirect light component with Batwing diffuser for wide-beam light exit; Direct light component with edge light and light-guide technology for homogenous light exit; DALI Load 1x; Integration into DALI light management systems; DALI - dimming via digital rotary dimmer; TouchDIM - dimming via standard switch

<sup>1)</sup> For luminaires with separate control gear, the luminous efficacy refers to the luminaire head without control gear