



H	$\Phi$ : 4100 lm	E   0°	D
0.50 m	C0-C180: 76°	9450 lx	C90-C270: 78° 0.78 m   0.81 m
1.00 m		2362 lx	1.55 m   1.61 m
1.50 m		1050 lx	2.33 m   2.42 m
2.00 m		591 lx	3.11 m   3.22 m
2.50 m		378 lx	3.88 m   4.03 m
3.00 m		262 lx	4.66 m   4.84 m
3.50 m		193 lx	5.43 m   5.64 m

## Work equipment

### Connected load

### Power consumption

### Standby

### Power factor

### Luminous flux

### Luminous efficiency <sup>1)</sup>

### Light type/color

### Colour temperatur

### Color rendering index

### Light distribution

### Beam angle

### Chromaticity tolerance LED

### Glare control

### Luminance (L65)

### UGR class (4H 8H; EN 12464-1)

### System of protection/Class <sup>2)</sup>

### Technology

### Operation

### Housing

### Mains lead

### Design

### Installation dimensions

### Life expectancy LED

### EAN

### Weight without/incl. packaging

### Packaging dimensions

### Special features

## Electronic ballast

220 - 240 V; 50 Hz; 60 Hz

ca. 30 W

ca. 0,5 W

env. 0,900

approx. 4.100 lm

approx. 136 lm/W

Cold white

approx. 4.000 K

CRI ≥ 80

Direct; approx. 100 %

76° / 78°

< 3 SDCM

Prism aperture

≤ 2.700 cd/m<sup>2</sup>

≤ 19

IP 20; 22; II

Continuously dimmable

External

Sectional aluminium; White

ca. 0,5 m; Connector

Integrated version

ca. 600 mm; 600 mm

L80B50 75.000h

4013330053079

ca. 2,9 kg; 3,5 kg

ca. 695 mm; 685 mm; 85 mm

Flicker-free; Direct light component with edge light and light-guide technology for homogenous light exit; DALI Load 1x; System dimension 600 x 600 mm; TouchDIM - dimming via standard switch; Strain relief with the possibility of through-wiring

<sup>1)</sup> For luminaires with separate control gear, the luminous efficacy refers to the luminaire head without control gear  
<sup>2)</sup> Higher degree of protection when installed.