



Light source
Work equipment
Connected load
Power consumption
Standby
Power factor
Luminous flux
Luminous efficiency ¹⁾
Light type/-color
Colour temperatur
Color rendering index
Light distribution
Beam angle
Chromaticity tolerance LED
Glare control
Luminance (L65)
UGR class (4H 8H; EN 12464-1)
System of protection/Class ²⁾
Technology
Operation
Housing
Mains lead
Design
Fastening
EAN
Weight without/incl. packaging
Packaging dimensions
Special features

LED
Electronic ballast
220 - 240 V; 50 Hz; 60 Hz
ca. 14 W
ca. 0,2 W
env. 0,90
approx. 1.400 lm
approx. 100 lm/W
Warm white
approx. 3.000 K
CRI ≥ 80
Direct; approx. 100 %
64°
< 3 SDCM
Prism aperture
≤ 2.100 cd/m²
≤ 19
IP 20; 22; II
Continuously dimmable
External
Sheet metal; White
ca. 0,35 m; Connector
Integrated version
Tension spring
4013330041557
ca. 0,7 kg; 0,9 kg
ca. 210 mm; 230 mm; 130 mm
Flicker-free; Integration into DALI light management systems; As supplement for room depths and walking areas; Suitable as emergency lighting; Ceiling installation without tools by means of tension springs; Low installation depth thanks to external ballast; TouchDIM - dimming via standard switch; Strain relief with the possibility of through-wiring

¹⁾ For luminaires with separate control gear, the luminous efficacy refers to the luminaire head without control gear
²⁾ Higher degree of protection when installed.