



Light source	LED
Work equipment	Adjustable electronic ballast, digital DALI
Connected load	220 - 240 V; 50 Hz; 60 Hz
Power consumption	ca. 26 W
Standby	ca. 0,15 W
Power factor	env. 0,98
Luminous flux	approx. 2.650 lm
Luminous efficiency ¹⁾	approx. 101 lm/W
Light type/-color	Warm white
Colour temperatur	approx. 3.000 K
Color rendering index	CRI ≥ 80
Light distribution	Direct; approx. 100 %
Chromaticity tolerance LED	< 3 SDCM
Glare control	Prism aperture
Luminance (L65)	≤ 3.000 cd/m ²
UGR class (4H 8H; EN 12464-1)	≤ 19
System of protection/Class	IP 40; I
Technology	Continuously dimmable
Operation	External
Housing	Sectional aluminium; Silver
Light source cover	Acrylic (PMMA); Clear
Mains lead	Connector; Middle luminaire
Design	mounted version
Fastening	Ceiling mounted
Life expectancy LED	L90B50 50.000h
EAN	4013330077549
Weight without/incl. packaging	ca. 7,3 kg; 9,6 kg
Dimensions (dimensional drawing)	L=2244mm
Packaging dimensions	ca. 2.410 mm; 190 mm; 120 mm
Special features	Flicker-free; DALI Load 1x; Suitable as emergency lighting; Through-wired, up to 18 m on one mains connection; Mechanical and electrical connection of the individual modules without tools; TouchDIM - dimming via standard switch

¹⁾ For luminaires with separate control gear, the luminous efficacy refers to the luminaire head without control g