



|  |   |
|--|---|
| <b>Light source</b>                      | LED   |
| <b>Work equipment</b>                    | Adjustable electronic ballast, digital DALI   |
| <b>Connected load</b>                    | 220 - 240 V; 50 Hz; 60 Hz   |
| <b>Power consumption</b>                 | ca. 10 W  |
| <b>Standby</b>                           | ca. 0,2 W   |
| <b>Power factor</b>                      | env. 0,97   |
| <b>Luminous flux</b>                     | approx. 1.000 lm  |
| <b>Luminous efficiency <sup>1)</sup></b> | approx. 100 lm/W  |
| <b>Light type/-color</b>                 | Warm white  |
| <b>Colour temperatur</b>                 | approx. 3.000 K   |
| <b>Color rendering index</b>             | CRI ≥ 80  |
| <b>Light distribution</b>                | Direct; approx. 100 %   |
| <b>Chromaticity tolerance LED</b>        | < 3 SDCM  |
| <b>Glare control</b>                     | Prism aperture  |
| <b>Luminance (L65)</b>                   | ≤ 3.000 cd/m <sup>2</sup>   |
| <b>UGR class (4H 8H; EN 12464-1)</b>     | ≤ 19  |
| <b>System of protection/Class</b>        | IP 40; I  |
| <b>Technology</b>                        | Continuously dimmable   |
| <b>Operation</b>                         | External  |
| <b>Housing</b>                           | Sectional aluminium; Silver   |
| <b>Light source cover</b>                | Acrylic (PMMA); Clear   |
| <b>Mains lead</b>                        | Connector; End luminaire  |
| <b>Design</b>                            | mounted version   |
| <b>Fastening</b>                         | Ceiling mounted   |
| <b>Life expectancy LED</b>               | L90B50 50.000h  |
| <b>EAN</b>                               | 4013330073114   |
| <b>Weight without/incl. packaging</b>    | ca. 3 kg; 4 kg  |
| <b>Dimensions (dimensional drawing)</b>  | L=848mm   |
| <b>Packaging dimensions</b>              | ca. 1.000 mm; 190 mm; 120 mm  |
| <b>Special features</b>                  | Flicker-free; DALI Load 1x; Suitable as emergency lighting; Through-wired, up to 18 m on one mains connection; Mechanical and electrical connection of the individual modules without tools; TouchDIM - dimming via standard switch |

<sup>1)</sup> For luminaires with separate control gear, the luminous efficacy refers to the luminaire head without control gear