



|  |                               |
|--|-------------------------------|
| <b>Work equipment</b>                    | Power supply unit             |
| <b>Connected load</b>                    | 220 - 240 V; AC; 50 Hz; 60 Hz |
| <b>Power consumption</b>                 | ca. 22 W                      |
| <b>Luminous flux</b>                     | approx. 2.100 lm              |
| <b>Luminous efficiency <sup>1)</sup></b> | approx. 95 lm/W               |
| <b>Light type/-color</b>                 | Warm white                    |
| <b>Colour temperatur</b>                 | approx. 3.000 K               |
| <b>Color rendering index</b>             | CRI ≥ 80                      |
| <b>Light distribution</b>                | Direct; approx. 84 %          |
| <b>Chromaticity tolerance LED</b>        | < 3 SDCM                      |
| <b>Glare control</b>                     | without                       |
| <b>Luminance (L65)</b>                   | ≤ 3.500 cd/m <sup>2</sup>     |
| <b>UGR class (4H 8H; EN 12464-1)</b>     | ≤ 22                          |
| <b>System of protection/Class</b>        | I                             |
| <b>Technology</b>                        | Continuously dimmable; DALI   |
| <b>Operation</b>                         | External                      |
| <b>Housing</b>                           | Sheet metal; Painted; White   |
| <b>Light source cover</b>                | Acrylic (PMMA); White opal    |
| <b>Mains lead</b>                        | Direct power supply           |
| <b>Design</b>                            | mounted version               |
| <b>Fastening</b>                         | Ceiling mounted               |
| <b>EAN</b>                               | 4013330147808                 |
| <b>Weight without/incl. packaging</b>    | ca. 1,2 kg; 1,3 kg            |
| <b>Packaging dimensions</b>              | ca. 380 mm; 380 mm; 95 mm     |
| <b>Special features</b>                  | DALI Load 1x                  |

<sup>1)</sup> For luminaires with separate control gear, the luminous efficacy refers to the luminaire head without control g