



|                                          |                                                                                                                                                                                                                                     |
|------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Light source</b>                      | LED                                                                                                                                                                                                                                 |
| <b>Work equipment</b>                    | Adjustable electronic ballast, digital DALI                                                                                                                                                                                         |
| <b>Connected load</b>                    | 220 - 240 V; 50 Hz; 60 Hz                                                                                                                                                                                                           |
| <b>Power consumption</b>                 | ca. 16 W                                                                                                                                                                                                                            |
| <b>Standby</b>                           | ca. 0,15 W                                                                                                                                                                                                                          |
| <b>Power factor</b>                      | env. 0,98                                                                                                                                                                                                                           |
| <b>Luminous flux</b>                     | approx. 1.700 lm                                                                                                                                                                                                                    |
| <b>Luminous efficiency <sup>1)</sup></b> | approx. 106 lm/W                                                                                                                                                                                                                    |
| <b>Light type/-color</b>                 | Cold white                                                                                                                                                                                                                          |
| <b>Colour temperatur</b>                 | approx. 4.000 K                                                                                                                                                                                                                     |
| <b>Color rendering index</b>             | CRI ≥ 80                                                                                                                                                                                                                            |
| <b>Light distribution</b>                | Direct; approx. 100 %                                                                                                                                                                                                               |
| <b>Chromaticity tolerance LED</b>        | < 3 SDCM                                                                                                                                                                                                                            |
| <b>Glare control</b>                     | Prism aperture                                                                                                                                                                                                                      |
| <b>Luminance (L65)</b>                   | ≤ 3.000 cd/m <sup>2</sup>                                                                                                                                                                                                           |
| <b>UGR class (4H 8H; EN 12464-1)</b>     | ≤ 19                                                                                                                                                                                                                                |
| <b>System of protection/Class</b>        | IP 40; I                                                                                                                                                                                                                            |
| <b>Technology</b>                        | Continuously dimmable                                                                                                                                                                                                               |
| <b>Operation</b>                         | External                                                                                                                                                                                                                            |
| <b>Housing</b>                           | Sectional aluminium; Silver                                                                                                                                                                                                         |
| <b>Light source cover</b>                | Acrylic (PMMA); Clear                                                                                                                                                                                                               |
| <b>Mains lead</b>                        | Connector; End luminaire                                                                                                                                                                                                            |
| <b>Design</b>                            | mounted version                                                                                                                                                                                                                     |
| <b>Fastening</b>                         | Ceiling mounted                                                                                                                                                                                                                     |
| <b>Life expectancy LED</b>               | L90B50 50.000h                                                                                                                                                                                                                      |
| <b>EAN</b>                               | 4013330077150                                                                                                                                                                                                                       |
| <b>Weight without/incl. packaging</b>    | ca. 4,6 kg; 6,1 kg                                                                                                                                                                                                                  |
| <b>Dimensions (dimensional drawing)</b>  | L=1408mm                                                                                                                                                                                                                            |
| <b>Packaging dimensions</b>              | ca. 1.600 mm; 190 mm; 120 mm                                                                                                                                                                                                        |
| <b>Special features</b>                  | Flicker-free; DALI Load 1x; Suitable as emergency lighting; Through-wired, up to 18 m on one mains connection; Mechanical and electrical connection of the individual modules without tools; TouchDIM - dimming via standard switch |

<sup>1)</sup> For luminaires with separate control gear, the luminous efficacy refers to the luminaire head without control gear