



Height (m)	Illuminance (lx)	Beam angle (°)
0.50 m	9450 lx	0.78 m 0.81 m
1.00 m	2362 lx	1.55 m 1.61 m
1.50 m	1050 lx	2.33 m 2.42 m
2.00 m	591 lx	3.11 m 3.22 m
2.50 m	378 lx	3.88 m 4.03 m
3.00 m	262 lx	4.66 m 4.84 m
3.50 m	193 lx	5.43 m 5.64 m

Work equipment

Connected load

Power consumption

Standby

Power factor

Luminous flux

Luminous efficiency ¹⁾

Light type/color

Colour temperatur

Color rendering index

Light distribution

Beam angle

Chromaticity tolerance LED

Glare control

Luminance (L65)

UGR class (4H 8H; EN 12464-1)

System of protection/Class ²⁾

Technology

Operation

Housing

Mains lead

Design

Installation dimensions

Life expectancy LED

EAN

Weight without/incl. packaging

Packaging dimensions

Special features

Electronic ballast

220 - 240 V; 50 Hz; 60 Hz

ca. 30 W

ca. 0,5 W

env. 0,900

approx. 4.100 lm

approx. 136 lm/W

Cold white

approx. 4.000 K

CRI \geq 80

Direct; approx. 100 %

76° / 78°

< 3 SDCM

Prism aperture

\leq 2.700 cd/m²

\leq 19

IP 20; 22; II

Continuously dimmable

External

Sectional aluminium; White

ca. 0,5 m; Connector

Integrated version

ca. 625 mm; 625 mm

L80B50 75.000h

4013330052447

ca. 3,1 kg; 3,7 kg

ca. 695 mm; 685 mm; 85 mm

Flicker-free; Direct light component with edge light and light-guide technology for homogenous light exit; DALI Load 1x; System dimension 625 x 625 mm; TouchDIM - dimming via standard switch; Strain relief with the possibility of through-wiring

¹⁾ For luminaires with separate control gear, the luminous efficacy refers to the luminaire head without control gear
²⁾ Higher degree of protection when installed.