


5 pin

D43 ↓24.6% ↑75.4% Φ: 6900 lm



**Work equipment**

**Connected load**

**Power consumption**

**Luminous flux**

**Luminous efficiency** <sup>1)</sup>

**Light type/-color**

**Colour temperatur**

**Color rendering index**

**Light distribution**

**Chromaticity tolerance LED**

**Glare control**

**System of protection/Class**

**Technology**

**Operation**

**Housing**

**Light source cover**

**Mains lead**

**Design**

**Fastening**

**Maximum ambient temperature**

**Life expectancy LED**

**EAN**

**Weight without/incl. packaging**

**Packaging dimensions**

**Special features**

**Power supply unit**

220 - 240 V; AC; 50 Hz; 60 Hz

ca. 64 W

approx. 7.090 lm

approx. 110 lm/W

Warm white

approx. 3.000 K

CRI ≥ 80

Direct/indirect

< 3 SDCM

Diffusor

IP 20; I

Switchable

Switch

Sectional aluminium; Anodised; Aluminium

coloured anodised

Acrylic (PMMA); White opal

Connector; 5 pin

mounted version

Wall bracket

25 °C

L80B50 50.000h

4013330146344

ca. 6,9 kg; 8,9 kg

ca. 133 mm; 400 mm; 1.185 mm

General light, indirect, 3000K, Ra≥80; Night light; indirect; 2700K; Ra≥80; Reading light, direct, 3,00K, Ra≥80; DIN EN 60598-2-25

<sup>1)</sup> For luminaires with separate control gear, the luminous efficacy refers to the luminaire head without control gear