



Work equipment

Connected load

Power consumption

Luminous flux

Luminous efficiency ¹⁾

Light type/-color

Colour temperatur

Color rendering index

Light distribution

Direct ratio

Chromaticity tolerance LED

Glare control

UGR class (4H 8H; EN 12464-1)

System of protection/Class

Technology

Operation

Emergency lighting

Housing

Light source cover

Mains lead

Design

Fastening

Minimum ambient temperature

Decorative contrast side parts

Life expectancy LED

EAN

Weight without/incl. packaging

Packaging dimensions

Special features

Power supply unit

220 - 240 V; AC; 50 Hz; 60 Hz

ca. 74 W

approx. 7.690 lm

approx. 103 lm/W

Warm white

approx. 3.000 K

CRI ≥ 80

Direct/indirect

approx. 28 %

< 3 SDCM

Diffusor

≤ 16

IP 20; C I

Two-stage switchable; -

External

none

Sectional aluminium; Anodised; Aluminium
coloured anodised
Acrylic (PMMA); White opal

Connection box; 3 pin

mounted version

Mounting rail

25 °C

White

L80B50 50.000h

4013330145859

ca. 4 kg; 5,8 kg

ca. 1.290; 385; 140

General light, indirect, 3000K, Ra≥80; Night light;
indirect; 2700K; Ra≥80; Reading light, direct, 3,00K,
Ra≥80; DIN EN 60598-2-25

¹⁾ For luminaires with separate control gear, the luminous efficacy refers to the luminaire head without control g