



$E 0^\circ$		
C0-C180: 77°	7842 lx	C90-C270: 79°
0.50 m		0.80 m 0.82 m
1.00 m	1960 lx	1.60 m 1.64 m
1.50 m	871 lx	2.40 m 2.47 m
2.00 m	490 lx	3.21 m 3.29 m
2.50 m	314 lx	4.01 m 4.11 m
3.00 m	218 lx	4.81 m 4.93 m
3.50 m	160 lx	5.61 m 5.76 m

Light source

Work equipment

Connected load

Secondary tension

Power consumption

Sec. power consumption

Luminous flux

Luminous efficiency ¹⁾

Light type/-color

Colour temperatur

Color rendering index

Light distribution

Beam angle

Chromaticity tolerance LED

Glare control

Luminance (L65)

UGR class (4H 8H; EN 12464-1)

System of protection/Class ²⁾

Technology

Operation

Housing

Mains lead

Design

Installation dimensions

Maximum ambient temperature

Life expectancy LED

EAN

Weight without/incl. packaging

Special features

LED

Power supply unit

220 - 240 V; 50 Hz; 60 Hz

24 V

ca. 31 W

ca. 27 W

approx. 3.500 lm

approx. 112 lm/W

Cold white

approx. 4.000 K

CRI \geq 90; R9 \geq 50

Direct; approx. 100 %

77°/79°

< 3 SDCM

Prism aperture

\leq 2.400 cd/m²

\leq 19

IP 40; 05; II

Continuously dimmable; DALI; Touch DIM

External

Sectional aluminium; White

ca. 0,8 m; Connector; 5 pin

Integrated version

ca. 625 mm; 625 mm; 40 mm

25 °C

L80B50 75.000h

4013330187453

ca. 3,1 kg

Flicker-free; Direct light component with edge light and light-guide technology for homogenous light exit; DALI Load 1x; System dimension 625 x 625 mm; Strain relief with the possibility of through-wiring

¹⁾ For luminaires with separate control gear, the luminous efficacy refers to the luminaire head without control gear
²⁾ Higher degree of protection when installed.

