


Recessed modular luminaire DOTOO.fit DFE 4000/840



114546000-00815305



CE



5 pin



E 0°		
0.50 m	9206 lx	0.84 m 0.84 m
1.00 m	2301 lx	1.68 m 1.68 m
1.50 m	1023 lx	2.52 m 2.52 m
2.00 m	575 lx	3.36 m 3.36 m
2.50 m	368 lx	4.20 m 4.20 m
3.00 m	256 lx	5.04 m 5.04 m
3.50 m	188 lx	5.88 m 5.88 m

Light source

Work equipment

Connected load

Secondary tension

Power consumption

Sec. power consumption

Luminous flux

Luminous efficiency ¹⁾

Light type/color

Colour temperatur

Color rendering index

Light distribution

Beam angle

Chromaticity tolerance LED

Glare control

Luminance (L65)

UGR class (4H 8H; EN 12464-1)

System of protection/Class ²⁾

Technology

Operation

Housing

Mains lead

Design

Installation dimensions

Maximum ambient temperature

Life expectancy LED

EAN

Weight without/incl. packaging

Special features

LED

Power supply unit

220 - 240 V; 50 Hz; 60 Hz

24 V

ca. 30 W

ca. 28 W

approx. 4.100 lm

approx. 136 lm/W

Cold white

approx. 4.000 K

CRI $\geq$ 80

Direct; approx. 100 %

80°

< 3 SDCM

Prism aperture

$\leq$ 3.000 cd/m²

$\leq$ 19

IP 40; 05; II

Switchable

External

Sectional aluminium; White

ca. 0,8 m; Connector; 5 pin

Integrated version

ca. 1.200 mm; 300 mm; 40 mm

25 °C

L80B50 75.000h

4013330187484

ca. 2,9 kg

Direct light component with edge light and light-guide technology for homogenous light exit

¹⁾ For luminaires with separate control gear, the luminous efficacy refers to the luminaire head without control gear.
²⁾ Higher degree of protection when installed.

Recessed modular luminaire DOTOO.fit
DFE 4000/840
114546000-00815305

