



Work equipment

Connected load

Power consumption

Standby

Luminous flux

Luminous efficiency ¹⁾

Light type/-color

Colour temperatur

Color rendering index

Light distribution

Chromaticity tolerance LED

UGR class (4H 8H; EN 12464-1)

System of protection/Class

Technology

Housing

Light source cover

Dimming Range

Mains lead

Design

Fastening

Minimum ambient temperature

Maximum ambient temperature

Life expectancy LED

DALI control

EAN

Weight without/incl. packaging

Special features

Adjustable electronic ballast, digital DALI

220 - 240 V; AC; 50 Hz; 60 Hz

ca. 46 W

ca. 0,25 W

approx. 6.200 lm

approx. 134 lm/W

adjustable white

approx. 2.700 - 6.500 K

CRI ≥ 90; R9 ≥ 50

Direct/indirect

< 3 SDCM

≤ 22

IP 40; I

Continuously dimmable; DALI

Aluminium; Powder coatet; Traffic white

Acrylic (PMMA); Clear; Structured

1-100%

Connector

mounted version

Available separately

-10 °C

30 °C

L90B50 50.000h

DT6 | Color control DT6

4013330193140

ca. 3,5 kg

Retrofittable; Indirect light component with Batwing diffuser for wide-beam light exit; Suitable as emergency lighting; Maintenance-friendly due to easily accessible ballasts; External control device required for DALI Device Type 6; Specified values at approx. 4000 K

¹⁾ For luminaires with separate control gear, the luminous efficacy refers to the luminaire head without control g