



#### Work equipment

#### Connected load

#### Power consumption

#### Standby

#### Luminous flux

#### Luminous efficiency <sup>1)</sup>

#### Light type/-color

#### Colour temperatur

#### Color rendering index

#### Light distribution

#### Chromaticity tolerance LED

#### UGR class (4H 8H; EN 12464-1)

#### System of protection/Class

#### Technology

#### Housing

#### Light source cover

#### Dimming Range

#### Mains lead

#### Design

#### Fastening

#### Minimum ambient temperature

#### Maximum ambient temperature

#### Life expectancy LED

#### DALI control

#### EAN

#### Weight without/incl. packaging

#### Product compatible with

#### Special features

Adjustable electronic ballast, digital DALI

220 - 240 V; AC; 50 Hz; 60 Hz

ca. 46 W

ca. 0,2 W

approx. 6.200 lm

approx. 134 lm/W

adjustable white

approx. 2.700 - 6.500 K

CRI ≥ 90; R9 ≥ 50

Direct/indirect

< 3 SDCM

≤ 22

IP 40; I

Continuously dimmable; DALI

Aluminium; Powder coatet; Traffic white

Acrylic (PMMA); Clear; Structured

1-100%

Connector

mounted version

Screws

-10 °C

30 °C

L90B50 50.000h

DT8 | Color Control DT8

4013330193126

ca. 4,1 kg

VANERA

Indirect light component with Batwing diffuser for wide-beam light exit; Suitable as emergency lighting; Maintenance-friendly due to easily accessible ballasts; External control required for Dali Device type 8; Constant luminous flux between 2700 and 6500 K; Specified values at approx. 4000 K; Strain relief with the possibility of through-wiring

<sup>1)</sup> For luminaires with separate control gear, the luminous efficacy refers to the luminaire head without control g