



- Work equipment**
- Connected load**
- Power consumption**
- Standby**
- Luminous flux**
- Luminous efficiency ¹⁾**
- Light type/-color**
- Colour temperatur**
- Color rendering index**
- Light distribution**
- Chromaticity tolerance LED**
- UGR class (4H 8H; EN 12464-1)**
- System of protection/Class**
- Technology**
- Housing**
- Light source cover**
- Dimming Range**
- Mains lead**
- Design**
- Fastening**
- Ambient temperature min./max**
- Life expectancy LED**
- DALI control**
- EAN**
- Weight without/incl. packaging**
- Packaging dimensions**
- Product compatible with**
- Special features**

Adjustable electronic ballast, digital DALI
 220 - 240 V; AC; 50 Hz; 60 Hz
 approx. 46 W
 approx. 0,2 W
 approx. 6.200 lm
 approx. 134 lm/W
 adjustable white
 approx. 2.700 - 6.500 K
 CRI ≥ 90; R9 ≥ 50
 Direct/indirect; approx. 42 %
 < 3 SDCM
 ≤ 22
 IP 40; I
 Continuously dimmable; DALI
 Aluminium; Powder coatet; Traffic white
 Acrylic (PMMA); Clear; Structured
 1-100%
 Connector
 mounted version
 Screws
 -10 °C; 30 °C
 L90B50 50.000h
 DT8 | Color Control DT8
 4013330193126
 approx. 4,1
 approx. 0 mm; 0 mm; 0 mm
 VANERA
 Indirect light component with Batwing diffuser for wide-beam light exit; Suitable as emergency lighting; Maintenance-friendly due to easily accessible ballasts; External control required for Dali Device type 8; Constant luminous flux between 2700 and 6500 K; Specified values at approx. 4000 K; Strain relief with the possibility of through-wiring

¹⁾ For luminaires with separate control gear, the luminous efficacy refers to the luminaire head without control g